Subpart E—Unmanned River Barges on Lake Michigan Routes

Source: USCG-1998-4623, 67 FR 19690, Apr. 23, 2002, unless otherwise noted.

§45.171 Purpose.

(a) This subpart establishes a special load line regime under which certain unmanned, river-service, dry-cargo barges may be exempted from the normal Great Lakes load line requirements while operating on certain Lake Michigan routes. Depending upon the

route, the barge may only need a limited service domestic voyage load line, or may be conditionally exempted from load line assignment.

(b) Except as provided in this subpart, barges operating on Lake Michigan must have either an international load line assignment issued in accordance with the International Convention on Load Lines, 1966, as amended, or a Great Lakes load line assignment issued in accordance with the requirements of this part.

(c) The requirements of this subpart are summarized in Table 45.171:

Table 45.171:

,	Load Line Requirements for Dry Cargo River Barges Operating on Lake Michigan	or Dry Cargo River Bar Lake Michigan	ges	
	Voyages	Voyages between Chicago (Calumet Harbor), IL and :	t Harbor), IL and :	
	Burns Harbor, IN	Milwaukee, WI	St. Joseph, MI	Muskegon, MI
1) Load line requirement	Conditionally exempted from load line assignment (must meet requirements below)	ad line assignment ints below)	"Limited service domestic voyage" load line	tic voyage" load line
2) Where to register/apply	Exempted barges must be registered with the USOG Marine Safety Office 215 W. 83" St., Suite D Burr Ridge, IL 60521	the USCG Marine Safety Office uite D 0521	Apply for load line to ABS Americas 16855 Northchase Dr. Houston, TX 77060	o ABS Americas chase Dr. X 77060
3) Eligible barges		Dry cargo river barges		
	Builta	Built and maintained in accordance with ABS River Rules Lenoth-to-deoth ratio less than 22	ABS River Rules n 22	
	No age limitation	Not more than 10 years old	No age limitation	nitation
4) Freeboard requirement	All barg	All barges: freeboard must be at least 24 inches (610 mm)	inches (610 mm)	
	Open hopper barges:	Open hopper barges: coaming height + freeboard must be at least 54 inches (1,372 mm)	oe at least 54 inches (1,372 mr	(i
5) Tow limitations		Barges must be unmanned	P	
		Not more than 5 nautical miles from shore	om shore	
	No limit on number of barges	Not	Not more than 3 barges per tow	
6) Cargo limitations	Dry cargoes only.	Dry cargoes only. Liquid cargoes, even in drums or tank containers, are prohibited	ank containers, are prohibited	
	No hazardous materials. Haz	No hazardous materials. HazMats are defined in 46 CFR part 148 and 49 CFR chapter 1, subchapter C	48 and 49 CFR chapter 1, subo	hapter C
7) Weather limitations		Ice conditions: adverse	ice conditions: adverse conditions that imperil tow or access to shelter	access to shelter
If conditions exceed these limits, voyage	: :		Waves: 4 feet (1.2 m)	
and vessel must proceed to shelter	"Fair weather" only	Sustained winds:	Sustained winds:	
		16 kts from NE, E, SE	16 kts from N, NW, W, SW	NW, W, SW
		Z I KIS ITOITI IN, INW, W, SW, S	ZI KIS ITOM INE, E, SE, S	Ξ, Ε, ΟΕ, Ο
8) Pre-departure preps:		Required as specified in § 45.191	5.191	
9) Towboat requirements		Sufficie	Sufficient to handle tow, but at least	
(a) Power:	Sufficient to handle tow	1,000 HP	무	1,500 HP
(b) Communication system:	Recommended § 45.195(a)	Recommended § 45.195(a)	· § 45.195(a)	Required § 45.195(a
(c) Cutting gear:	Recommended § 45.195(b)	Recommended § 45.195(b)	· § 45.195(b)	Required § 45.195(b
(d) Operational plan:	Recommended § 45.197	Recommended § 45.197	§ 45.197	Required § 45.197

$\S 45.173$ Eligible barges.

Only barges meeting the following requirements are eligible for the special load line regime under this subpart:

- (a) Unmanned, river service, drycargo barges;
- (b) Barges that have been designed and built to at least the minimum scantlings of the American Bureau of Shipping River Rules which were in effect at the time of construction;